

VARIO | VARIO+

4G LTE SPECIFICATION



2 BUTTON VARIO | 10 BUTTON VARIO | 7 BUTTON VARIO ENGRAVED
(AVAILABLE WITH 2-10 CALL BUTTONS WITHOUT KEYPAD)



3 BUTTON VARIO+ | 2 BUTTON VARIO+ VINYL LABELS | 3 BUTTON VARIO PROX
(AVAILABLE WITH 2-6 CALL BUTTONS WITH KEYPAD | 2-6 CALL BUTTONS WITH PROX)

- 316 marine grade stainless steel faceplate
- Low profile, high strength, sealed back box for greater performance and durability
- LED downlight
- Surface mounted
- Downward facing microphone
- **THS** Horwood quality sound
- 7 call divers
- IP64 rated keypad (where keypad is fitted)
- Time clock with 9 profiles
- Optional integrated backlight, vandal resistant keypad
- Timed 'Trade' button (where keypad is fitted)
- 400 PIN codes for coded entry
- 900 Authorised dial to open numbers
- Event SMS alerts
- Aux triggered SMS alerts
- Dimensions: H 286mm x W 126mm x D 40mm

FEATURES AND BENEFITS



EASY TO USE

- Each call point has the ability to cascade through 8 landline or mobile numbers. Once answered, if the recipient wants to grant access to the visitor they simply press the # key on their phone.



DOWNLOADABLE ACTIVITY LOGS

- Download the last 10,000 interactions with the unit and see who is gaining entry, how and when.
- A great security feature for free!



ACCESS CONTROL

- With built in keypad and dial to open, you can authorise entry to specific individuals with either a PIN code or by registering their mobile number. You can even time restrict entry for certain individuals if required!



EASY TO INSTALL

- Minimal cabling:
 - Simply plug (12v) PSU into 240V AC power.
 - Connect relays into entry equipment.
 - Connect antenna and register onto to local mobile network (TG Telecom SIM provided upon request*).
- No access is required to individual properties for installations or maintenance.



CONFIGURATION

- Standalone as standard. Available in Hub and Satellite set up.
- Integration with supplementary TelPad.



TWO YEAR WARRANTY

- Including programming support.
- Thereafter, select your level of cover in line with your specific site requirements.

* Subject to activation order.

TECHNICAL SPECIFICATION

- **POWER:** 12 Volt 1 Amp. DC PSU fitted with a 3A fuse (*supplied and must be dedicated to the Telguard intercom unit*). Power Consumption: 120 mA Idle @ 12 Volts.
- **TELEPHONE TYPE:** Standard DTMF (*Dual Tone Multi Frequency*) generating telephone, cordless or mobile phone. (*Note that VoIP phones may require additional setup to use the DTMF standard*).
- **PROGRAMMING:** Remotely programmable via App or SMS. Locally via USB cable.
- **RELAYS:** 3: 1 x 2A, 2 x 200mA, 2 x Auxiliary inputs.
- **RELAY ACTIVATION TIME:** 1 ~ 60 seconds, adjustable locally and remotely.
- **OPERATING COMMANDS:** Default #, 2#, 3#, 4#, 5#, 6#, 7#, 8#, 9#. All relay commands are configurable.
- **TIME CLOCKS:** The on board time clock enables custom profile functions to be activated.
- **AUTHORISED CALL ACCESS:** 900 telephone numbers can be stored. Calling the unit, from an authorised telephone number activates a predetermined relay.
- **VOLUME:** Adjustable 1 ~ 9 levels.
- **RECOMMENDATION (when using Hub & Satellite configuration):** Use 8 Core CAT 5 Cable:
 - Twisted pair x2 Mic
 - Twisted pair x2 Speaker
 - Twisted pair x2 CAN
 - Twisted pair x2 Power
- **CABLE DISTANCE (when using Hub & Satellite configuration):** 300m

DOWNLOAD THE 'Commtel CONTROL' APP

- Entrances are easily controlled from your smartphone!



■ Please pay particular attention to the Safety Message Contents included on the App front page (*View Safety Message*).



OPEN | LATCH | CLOSE
at the click of a button

EU CE Declaration of Conformity and Radio Equipment Directive is available at www.commtel-uk.com | GB-RH10 9RB



Raising Standards
Safety Assured

